

## B. AMENDMENTS TO CLAIMS

Please amend the claims as indicated hereinafter.

1 (CURRENTLY AMENDED) A method for maintaining data integrity, comprising the  
2 computer-implemented steps of:

3 generating checksum data by performing a physical checksum calculation on a block of

4 ~~data in volatile memory;~~ data;

5 after generating said checksum data,

6 performing a logical check on data contained within the block of data; and

7 if the block of data passes said logical check, then causing the block of data to be

8 written to nonvolatile memory.

1 2. (ORIGINAL) The method of Claim 1 wherein the steps of generating checksum data and  
2 performing a logical check are performed in response to a request to write said block of  
3 data to nonvolatile memory.

1 3. (ORIGINAL) The method of Claim 1 further comprising the step of writing the  
2 checksum data to nonvolatile memory in association with writing said block of data to  
3 nonvolatile memory.

1 4. (ORIGINAL) The method as recited in Claim 3, further comprising the steps of:  
2 after writing the block of data to nonvolatile memory,  
3 causing the block of data and said checksum data to be read from nonvolatile  
4 memory; and  
5 performing a physical checksum verification procedure on said block of data  
6 based on said checksum data, wherein the physical checksum verification

Sub  
CL

procedure indicates whether the block of data was corrupted subsequent to performing the logical check on the data contained with the block of data.

5. (ORIGINAL) The method as recited in Claim 1, further comprising the step of performing one or more physical checksum verification procedures prior to writing the block of data to nonvolatile memory, wherein the one or more physical checksum verification procedures indicate whether the block of data was corrupted subsequent to generating said checksum data.

6. (ORIGINAL) The method as recited in Claim 1, wherein:  
the step of performing a physical checksum calculation comprises the step of a software application performing the physical checksum calculation on said block of data;  
and  
the step of performing a logical check on data contained with the block of data comprises the step of said software application performing the logical check on data contained with the block of data.

7. (ORIGINAL) The method as recited in Claim 4, wherein:  
the step of performing a physical checksum calculation comprises the step of an software application performing the physical checksum calculation on said block of data;  
the step of performing a logical check on data contained with the block of data comprises the step of said software application performing the logical check on data contained with the block of data; and

7 Sub  
8 Cl

the step of performing a physical checksum verification procedure on said block of data comprises the step of said software application performing the physical checksum verification procedure on said block of data.

1 8. (ORIGINAL) The method as recited in Claim 5, wherein:

2 the step of performing a physical checksum calculation comprises the step of an software  
3 application performing the physical checksum calculation on said block of data;  
4 the step of performing a logical check on data contained with the block of data comprises  
5 the step of said software application performing the logical check on data  
6 contained with the block of data; and

7 the step of performing one or more physical checksum verification procedures prior to  
8 writing the block of data to nonvolatile memory comprises the step of one or more  
9 components other than said software application performing the one or more  
10 physical checksum verification procedures prior to writing the block of data to  
11 nonvolatile memory.

1 9. (ORIGINAL) The method as recited in Claim 4, further comprising the step of:

2 after performing the physical checksum verification procedure on said block of data,  
3 storing the block of data as a backup version of the block of data, wherein the  
4 backup version of the block of data is maintained separate from said block of data  
5 in said nonvolatile memory.

103

10. (WITHDRAWN) A method for storing data in a nonvolatile memory, comprising the  
2 computer-implemented steps of:  
3 determining a desired location in said nonvolatile memory for storing a data block;

4 inserting an address value in said data block, wherein the address value identifies the  
5 desired location;  
6 prior to performing an operation that stores the data block to the nonvolatile memory,  
7 verifying that the address value contained within the data block correctly  
8 identifies the location in nonvolatile memory into which the operation is going to  
9 store the data block; and  
10 performing the operation to store the data block to the nonvolatile memory only if the  
11 address value contained within the data block correctly identifies the desired  
12 location in nonvolatile memory into which the operation is going to store the data  
13 block.

11. (WITHDRAWN) The method as recited in Claim 10, further comprising the steps of:  
after storing the block of data to nonvolatile memory,  
reading the block of data from a location in nonvolatile memory; and  
determining, based upon the address value contained within the data block, whether the  
block of data was read from the desired location in the nonvolatile memory.

12. (WITHDRAWN) The method as recited in Claim 10, further comprising the step of  
maintaining a mapping that identifies a specific location in said nonvolatile memory into  
which said data block is to be stored.

13. (WITHDRAWN) The method as recited in Claim 10, wherein:  
the step of determining a location in said nonvolatile memory comprises the step of  
determining a plurality of locations in said nonvolatile memory for storing said  
data block;

5 the step of inserting an address value in said data block, comprises the step of inserting a  
6 plurality of address values in said data block, wherein the plurality of address  
7 values identify multiple locations in said nonvolatile memory for which the data  
8 block is to be stored; and  
9 the step of storing the data block to nonvolatile memory comprises the step of storing the  
10 data block in each of the multiple locations in nonvolatile memory only after  
11 verifying the plurality of address values includes an address value that correctly  
12 identifies the location in nonvolatile memory into which the data block is to be  
13 stored.

14. (ORIGINAL) A method for maintaining data integrity, comprising the computer-  
implemented steps of:  
performing a physical checksum calculation on a block of data;  
after performing the physical checksum calculation,  
performing a first physical checksum verification procedure on said block of data  
prior to writing the block of data to nonvolatile memory, wherein the first  
physical checksum verification procedure indicates whether the block of  
data was corrupted subsequent to performing the physical checksum  
calculation on the data contained with the block of data; and  
if the block of data passes said first physical checksum verification procedure,  
then causing the block of data to be written to nonvolatile memory.

15. (ORIGINAL) The method as recited in Claim 14, further comprising the steps of:  
after writing the block of data to nonvolatile memory,  
causing the block of data to be read from nonvolatile memory; and

Sub  
Cl

performing a second physical checksum verification procedure on said block of data, wherein the second physical checksum verification procedure indicates whether the block of data was corrupted subsequent to performing the first physical checksum verification procedure on the data contained with the block of data.

16. (ORIGINAL) The method as recited in Claim 14, wherein the step of performing a first physical checksum verification procedure includes the steps of performing a plurality of physical checksum verification procedures on said block of data prior to writing the block of data to nonvolatile memory, wherein the plurality of physical checksum verification procedures indicate whether the block of data was corrupted subsequent to performing the physical checksum calculation on the data contained with the block of data.

17. (ORIGINAL) The method as recited in Claim 14, wherein:  
the step of performing a physical checksum calculation comprises the step of a software application performing the physical checksum calculation on said block of data;  
and  
the step of performing a first physical checksum verification procedure on said block of data comprises the step of a component other than said software application performing said first physical checksum verification procedure on said block of data prior to writing the block of data to nonvolatile memory.

18. (ORIGINAL) The method as recited in Claim 17, wherein the step of performing a physical checksum verification procedure on said block of data comprises the step of a disk array component performing the physical checksum verification procedure on said

SA  
4 block of data, wherein the disk array component is configured to write the block of data  
5 to disk only after verifying the integrity of the data block.

B3  
1 19. (ORIGINAL) The method as recited in Claim 14, further comprising the step of:  
2 after performing the physical checksum calculation,  
3 performing a logical check on data contained with the block of data; and  
4 if the block of data does not pass said logical check, then not writing the block of  
5 data to nonvolatile memory.

B4  
1 20. (PREVIOUSLY PRESENTED) The method as recited in Claim 19, wherein:  
2 the step of performing a physical checksum calculation comprises the step of an software  
3 application performing the physical checksum calculation on said block of data;  
4 the step of performing a logical check on data contained with the block of data comprises  
5 the step of said software application performing the logical check on data  
6 contained with the block of data; and  
7 the step of performing a first physical checksum verification procedure prior to writing  
8 the block of data to nonvolatile memory comprises the step of one or more  
9 components other than said software application performing one or more physical  
10 checksum verification procedures prior to writing the block of data to nonvolatile  
11 memory.

B5  
1 21. (WITHDRAWN) The method as recited in Claim 11, wherein the step of determining,  
2 based upon the address value contained within the data block, whether the block of data  
3 was read from the desired location in the nonvolatile memory includes comparing at least

4 a portion of the address value contained within the data block with data that indicates the  
5 location in nonvolatile memory from which the data block was read.

1 22. (WITHDRAWN) The method as recited in Claim 10, wherein:

2 the step of verifying that the address value contained within the data block  
3 correctly identifies the location in nonvolatile memory into which  
4 the operation is going to store the data block is performed by a  
5 storage device, and

6 the step of performing the operation to store the data block to the  
7 nonvolatile memory only if the address value contained within the  
8 data block correctly identifies the desired location in nonvolatile  
9 memory into which the operation is going to store the data block is  
10 performed by the storage device.

1 23. (CURRENTLY AMENDED) A computer-readable medium for maintaining data  
2 integrity, the computer-readable medium carrying one or more sequences of one or more  
3 instructions which, when executed by one or more processors, cause the one or more  
4 processors to perform the steps of:

5 generating checksum data by performing a physical checksum calculation on a block of  
6 ~~data in volatile memory;~~ data;

7 after generating said checksum data,

8 performing a logical check on data contained within the block of data; and

9 if the block of data passes said logical check, then causing the block of data to be

10 written to nonvolatile memory.

Subs  
C1

1 24. (PREVIOUSLY PRESENTED) The computer-readable medium of Claim 23 wherein the  
2 steps of generating checksum data and performing a logical check are performed in  
3 response to a request to write said block of data to nonvolatile memory.

1 25. (PREVIOUSLY PRESENTED) The computer-readable medium of Claim 23 further  
2 comprising one or more sequences of additional instructions which, when executed by  
3 the one or more processors, cause the one or more processors to perform the step of  
4 writing the checksum data to nonvolatile memory in association with writing said block  
5 of data to nonvolatile memory.

1 26. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 25,  
2 further comprising one or more sequences of additional instructions which, when  
3 executed by the one or more processors, cause the one or more processors to perform the  
4 steps of:  
5 after writing the block of data to nonvolatile memory,

6 causing the block of data and said checksum data to be read from nonvolatile  
7 memory; and

8 performing a physical checksum verification procedure on said block of data  
9 based on said checksum data, wherein the physical checksum verification  
10 procedure indicates whether the block of data was corrupted subsequent to  
11 performing the logical check on the data contained with the block of data.

1 27. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 23,  
2 further comprising one or more sequences of additional instructions which, when  
3 executed by the one or more processors, cause the one or more processors to perform the

Sub  
C1

4 step of performing one or more physical checksum verification procedures prior to  
5 writing the block of data to nonvolatile memory, wherein the one or more physical  
6 checksum verification procedures indicate whether the block of data was corrupted  
7 subsequent to generating said checksum data.

1 28. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 23,  
2 wherein:

3 the step of performing a physical checksum calculation comprises the step of a software  
4 application performing the physical checksum calculation on said block of data;

5 and

6 the step of performing a logical check on data contained with the block of data comprises

7 the step of said software application performing the logical check on data  
8 contained with the block of data.

1 29. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 26,  
2 wherein:

3 the step of performing a physical checksum calculation comprises the step of an software

4 application performing the physical checksum calculation on said block of data;

5 the step of performing a logical check on data contained with the block of data comprises

6 the step of said software application performing the logical check on data

7 contained with the block of data; and

8 the step of performing a physical checksum verification procedure on said block of data

9 comprises the step of said software application performing the physical checksum

10 verification procedure on said block of data.

Sw  
a

1 30. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 27,  
2 wherein:  
3 the step of performing a physical checksum calculation comprises the step of an software  
4 application performing the physical checksum calculation on said block of data;  
5 the step of performing a logical check on data contained with the block of data comprises  
6 the step of said software application performing the logical check on data  
7 contained with the block of data; and  
8 the step of performing one or more physical checksum verification procedures prior to  
9 writing the block of data to nonvolatile memory comprises the step of one or more  
10 components other than said software application performing the one or more  
11 physical checksum verification procedures prior to writing the block of data to  
12 nonvolatile memory.

Am

1 31. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 26,  
2 further comprising one or more sequences of additional instructions which, when  
3 executed by the one or more processors, cause the one or more processors to perform the  
4 step of:  
5 after performing the physical checksum verification procedure on said block of data,  
6 storing the block of data as a backup version of the block of data, wherein the  
7 backup version of the block of data is maintained separate from said block of data  
8 in said nonvolatile memory.

1 32. (WITHDRAWN) A computer-readable medium for storing data in a nonvolatile memory,  
2 the computer-readable medium carrying one or more sequences of one or more

3 instructions which, when executed by one or more processors, cause the one or more  
4 processors to perform the steps of:  
5 determining a desired location in said nonvolatile memory for storing a data block;  
6 inserting an address value in said data block, wherein the address value identifies the  
7 desired location;  
8 prior to performing an operation that stores the data block to the nonvolatile memory,  
9 verifying that the address value contained within the data block correctly  
10 identifies the location in nonvolatile memory into which the operation is going to  
11 store the data block; and  
12 performing the operation to store the data block to the nonvolatile memory only if the  
13 address value contained within the data block correctly identifies the desired  
14 location in nonvolatile memory into which the operation is going to store the data  
15 block.

1 33. (WITHDRAWN) The computer-readable medium as recited in Claim 32, further  
2 comprising one or more sequences of additional instructions which, when executed by  
3 the one or more processors, cause the one or more processors to perform the steps of:  
4 after storing the block of data to nonvolatile memory,  
5 reading the block of data from a location in nonvolatile memory; and  
6 determining, based upon the address value contained within the data block, whether the  
7 block of data was read from the desired location in the nonvolatile memory.

1 34. (WITHDRAWN) The computer-readable medium as recited in Claim 32, further  
2 comprising one or more sequences of additional instructions which, when executed by  
3 the one or more processors, cause the one or more processors to perform the step of

4 maintaining a mapping that identifies a specific location in said nonvolatile memory into  
5 which said data block is to be stored.

1 35. (WITHDRAWN) The computer-readable medium as recited in Claim 32, wherein:

2 the step of determining a location in said nonvolatile memory comprises the step of

3 determining a plurality of locations in said nonvolatile memory for storing said  
4 data block;

5 the step of inserting an address value in said data block, comprises the step of inserting a

6 plurality of address values in said data block, wherein the plurality of address  
7 values identify multiple locations in said nonvolatile memory for which the data  
8 block is to be stored; and

9 the step of storing the data block to nonvolatile memory comprises the step of storing the

10 data block in each of the multiple locations in nonvolatile memory only after

11 verifying the plurality of address values includes an address value that correctly

12 identifies the location in nonvolatile memory into which the data block is to be

13 stored.

1 36. (WITHDRAWN) The computer-readable medium as recited in Claim 33,

2 wherein the step of determining, based upon the address value contained

3 within the data block, whether the block of data was read from the desired

4 location in the nonvolatile memory includes comparing at least a portion of

5 the address value contained within the data block with data that indicates the

6 location in nonvolatile memory from which the data block was read.

1 37. (WITHDRAWN) The computer-readable medium as recited in Claim 32,  
2 wherein:  
3 the step of verifying that the address value contained within the data block  
4 correctly identifies the location in nonvolatile memory into which  
5 the operation is going to store the data block is performed by a  
6 storage device, and  
7 the step of performing the operation to store the data block to the  
8 nonvolatile memory only if the address value contained within the  
9 data block correctly identifies the desired location in nonvolatile  
10 memory into which the operation is going to store the data block is  
11 performed by the storage device.

Sub C1  
1 38. (PREVIOUSLY PRESENTED) A computer-readable medium for storing data in a  
2 nonvolatile memory, the computer-readable medium carrying one or more sequences of  
3 one or more instructions which, when executed by one or more processors, cause the one  
4 or more processors to perform the steps of:  
5 performing a physical checksum calculation on a block of data;  
6 after performing the physical checksum calculation,  
7 performing a first physical checksum verification procedure on said block of data  
8 prior to writing the block of data to nonvolatile memory, wherein the first  
9 physical checksum verification procedure indicates whether the block of  
10 data was corrupted subsequent to performing the physical checksum  
11 calculation on the data contained with the block of data; and

12 Sub  
13 Cl  
if the block of data passes said first physical checksum verification procedure,  
then causing the block of data to be written to nonvolatile memory.

1 39. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 38,  
2 further comprising one or more sequences of additional instructions which, when  
3 executed by the one or more processors, cause the one or more processors to perform the  
4 steps of:  
5 after writing the block of data to nonvolatile memory,  
6 causing the block of data to be read from nonvolatile memory; and  
7 performing a second physical checksum verification procedure on said block of  
8 data, wherein the second physical checksum verification procedure  
9 indicates whether the block of data was corrupted subsequent to  
10 performing the first physical checksum verification procedure on the data  
11 contained with the block of data.

1 40. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 38,  
2 wherein the step of performing a first physical checksum verification procedure includes  
3 the steps of performing a plurality of physical checksum verification procedures on said  
4 block of data prior to writing the block of data to nonvolatile memory, wherein the  
5 plurality of physical checksum verification procedures indicate whether the block of data  
6 was corrupted subsequent to performing the physical checksum calculation on the data  
7 contained with the block of data.

1 41. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 38,  
2 wherein:

3 the step of performing a physical checksum calculation comprises the step of a software  
4 application performing the physical checksum calculation on said block of data;  
5 and  
6 the step of performing a first physical checksum verification procedure on said block of  
7 data comprises the step of a component other than said software application  
8 performing said first physical checksum verification procedure on said block of  
9 data prior to writing the block of data to nonvolatile memory.

1 42. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 41,  
2 wherein the step of performing a physical checksum verification procedure on said block  
3 of data comprises the step of a disk array component performing the physical checksum  
4 verification procedure on said block of data, wherein the disk array component is  
5 configured to write the block of data to disk only after verifying the integrity of the data  
6 block.

1 43. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 38,  
2 further comprising one or more sequences of additional instructions which, when  
3 executed by the one or more processors, cause the one or more processors to perform the  
4 step of:  
5 after performing the physical checksum calculation,  
6 performing a logical check on data contained with the block of data; and  
7 if the block of data does not pass said logical check, then not writing the block of  
8 data to nonvolatile memory.

1 44. (PREVIOUSLY PRESENTED) The computer-readable medium as recited in Claim 43,  
2 wherein:  
3 the step of performing a physical checksum calculation comprises the step of an software  
4 application performing the physical checksum calculation on said block of data;  
5 the step of performing a logical check on data contained with the block of data comprises  
6 the step of said software application performing the logical check on data  
7 contained with the block of data; and  
8 the step of performing a first physical checksum verification procedure prior to writing  
9 the block of data to nonvolatile memory comprises the step of one or more  
10 components other than said software application performing one or more physical  
11 checksum verification procedures prior to writing the block of data to nonvolatile  
12 memory.

Sub  
Cl  
1 45. (PREVIOUSLY PRESENTED) A storage device comprising:  
2 a storage medium; and  
3 a storage mechanism communicatively coupled to the storage medium, the storage  
4 mechanism being configured to:  
5 perform a set of one or more verifications on a block of data prior to  
6 allowing the block of data to be written to the storage medium,  
7 wherein the set of one or more verifications includes a physical  
8 checksum verification that indicates whether the block of data was  
9 corrupted subsequent to a physical checksum calculation being  
10 performed on the data contained with the block of data, and

11 if the block of data passes the set of verifications, then allow the block of  
12 data to be written to the storage medium.

1 46. (PREVIOUSLY PRESENTED) The storage device as recited in Claim 45, wherein the  
2 set of verifications includes a logical check on the data contained within the block of data.

1 47. (PREVIOUSLY PRESENTED) The storage device as recited in Claim 46, wherein the  
2 storage mechanism is further configured to perform the logical check after the physical  
3 checksum verification.

1 48. (PREVIOUSLY PRESENTED) The storage device as recited in Claim 45, wherein the  
2 storage mechanism is further configured to:  
3 cause the block of data to be read from the storage medium, and  
4 perform a second physical checksum verification on the block of data that indicates  
5 whether the block of data was corrupted subsequent to the prior physical  
6 checksum verification being performed on the block of data.

1 49. (PREVIOUSLY PRESENTED) A storage device comprising:  
2 a storage medium; and  
3 a storage mechanism communicatively coupled to the storage medium, the storage  
4 mechanism being configured to:  
5 perform a logical check on data contained in a block of data after a physical  
6 checksum calculation has previously been performed on the block of data,  
7 and  
8 if the block of data passes the logical check, then allowing the block of data to be  
9 written to the storage medium.